

RD200

USB RFID Desktop Reader

Feature

- USB keyboard emulation, plug and play or serial port emulation(RS232).
- Built-in antenna, two colors led visual indication and buzzer alert.
- Auto-detect card and UID or block data.
- Provide API development tool.
- Update firmware through usb interface without disassembling case.
- Support decimal and hexadecimal ID formats.
- Unique serial number for identification.
- Built-in user data storage space.
- Development Tools: Support BCB6,VB6,VB.NET sample program and VC,VB,BCB, DevC,C# library.



Tag Supported :
EM / TEMIC / HiTag S / ISO-14443A



• PC Authentication



• Print control



• Program Development



• ID Identification



• Access Control



• Password Login



125 KHz



13.56 MHz



134.2 KHz

Specification

Specs / Item	RD200-LF	RD200-M1
Transmit Frequency	125KHz / 134.2KHz	13.56MHz
Card Compatibility	EM4100 compatible class / SYRIS/ FDX-B (ISO11784)	ISO-14443A (Mifare IK S50 / 4K S70 4/7 -byte UID / Mifare Ultralight)
Read Range	0 ~ 6 cm	0 ~ 7.5 cm
Communication	Compatible with versions 2.0, mini USB 5-pin connector	
Antenna	Built-in	
LED Indicator	Two-color LED visual indication	
Beep Tone	Built-in Buzzer	
Input Voltage	USB power , 5V / 200mA	
Operating Temperature	-20°C ~ +65°C · 5 ~ 95% RH	
Storage Temperature	-30°C ~ +85°C · 5 ~ 95% RH	
Dimensions (W x H x D)	105 x 72 x 16 mm	



- Reader with magnetic back housing which can be held on metal materials (OA partition, PC outer case...etc.)

Ordering Information

Item	Type
RD200-LF	USB RFID Desktop Reader- EM
RD200-M1	USB RFID Desktop Reader- Mifare